

# SA NO. 30 SOLVENT

PRODUCT CODE: 009-SA30S

## SOLVENT BLEND THINNER FOR CLEAN-UP

### PRODUCT DESCRIPTION

**SA No. 30 Solvent** is made up of a strong blend of aromatic and ketone solvents and surfactants. It is to be used as a paint or coating thinner, or for clean-up of solvent based acrylic sealers and similar.

### BENEFITS/FEATURES

- ◆ Strong, fast drying formula
- ◆ Easily melts down solvent based acrylics for easy clean up.
- ◆ Simply a contractor favorite

### RECOMMENDED APPLICATIONS

**SA No. 30 Solvent** is recommended for use as a paint/coating thinner or for clean-up of solvent based acrylic sealers and similar.

### TECHNICAL INFORMATION

Solids.....	0%	Wet Appearance.....	Clear
Drying Time.....	N/A	Dry Appearance.....	N/A
Re-Coat Time.....	N/A	VOC Content.....	N/A
Foot Traffic.....	N/A	Blush Resistance.....	N/A
Wheel Traffic.....	N/A	Solvent Resistance.....	N/A
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	N/A

\*\*\*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

### SPECIFICATIONS/COMPLIANCES

Not Applicable

### APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Coat</u>	<u>Optional Second Coat</u>
N/A	N/A	N/A

\*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

### SHELF LIFE

**SA No. 30 Solvent** has a shelf life of up to two years in it's original, sealed, unopened container.

### PACKAGING

**SA No. 30 Solvent** is packaged in 1 gallon cans, 5 gallon pails, and 55 gallon drums.

# SURFKOAT™

### SURFACE KOATINGS, INC.

134 Davis St. Portland, TN 37148  
 Phone: (615) 323-9461 Fax: (615) 323-9816  
 Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)

MISCELLANEOUS PRODUCTS

SA NO. 30 SOLVENT

## INSTRUCTIONS FOR USE

Uses may vary.

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and inadequate film formation or performance expectations may be limited.

## CLEAN-UP

Not Applicable.

## PRODUCT REMOVAL

Not Applicable.

## PRECAUTIONS AND LIMITATIONS

- ▶ **SA No. 30 Solvent** will not freeze during storage, however, storage above 50 F is recommended.
- ▶ All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- ▶ Keep away from open flames. **SA No. 30 Solvent** is flammable and is very susceptible to ignition.
- ▶ **SA No. 30 Solvent** was designed as a strong solvent solution for clean up. Other uses may be illegal.
- ▶ It is not recommended to thin **SA No. 30 Solvent**.
- ▶ Test prior to use.

## SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-323-9461.

**SURFKOAT™**

### **SURFACE KOATINGS, INC.**

134 Davis St. Portland, TN 37148  
Phone: (615) 323-9461 Fax: (615) 323-9816  
Visit us online at: [www.SurfKcoat.com](http://www.SurfKcoat.com)