



Maintenance

The complete solution for concrete needs.

SURFKOAT™

Surface Koatings, Inc. 134 Davis Street Portland, TN 37148
Ph: 615.323.9461 Fax: 615.323.9816 www.SurfKoat.com

© 2011 by Surface Koatings, Inc. All rights reserved.

APPLICATION ACCESSORIES

Surface Koatings, Inc. also offers a complete line SP Systems industrial sprayers, as well as many other application accessories including but not limited to:

- Acid Stain Sprayers
- Acetone Sprayers
- Concrete Sealer Sprayers
- Accessories for Sprayers
- Rollers (various sizes)
- Roller Frame Assemblies
- Acid Scrub Brushes
- and much more...



Proudly Distributed By:



Maintenance

Interior Wax/Polish Systems

Product Guide



SURFKOAT™

Surface Koatings, Inc.

Manufacturers of Industrial and Decorative Concrete Materials

Cherry SURF WAX

TOP KOAT HIGH PERFORMANCE

Cherry Surf-Wax is a cherry scented water based acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. Cherry Surf-Wax yields rapid gloss build along with superior long term wear characteristics. It's superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. Cherry Surf-Wax should be used on any sealed surface where a rapidly high gloss build and superior maintenance properties are desired. Should be considered an economical workhorse.

****Also Available in a Matte Finish Formula!***

Solids.....	21%
Drying Time.....	1-2 hours
Re-Coat Time.....	2-3 hours
Foot Traffic.....	12-24 hours
Wheel Traffic.....	24-48 hours
Application Temp.....	40°F - 85°F
Wet Appearance.....	Milky White
Dry Appearance.....	Crystal Clear
VOC Content.....	none
Blush Resistance.....	Excellent
Solvent Resistance.....	Good
Concrete Adhesion.....	Superior (over sealed surfaces)

Top Coat is a high performance cherry scented water based acrylic floor finish. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. Top Coat yields rapid high gloss build along with superior long term wear characteristics. It's superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. Top Coat should be used on any sealed surface where a rapidly high gloss build and superior maintenance properties are desired. Use Top Coat for extreme sheen and durability.

Solids.....	28%
Drying Time.....	1-2 hours
Re-Coat Time.....	2-3 hours
Foot Traffic.....	12-24 hours
Wheel Traffic.....	24-48 hours
Application Temp.....	40°F - 85°F
Wet Appearance.....	Milky White
Dry Appearance.....	Crystal Clear
VOC Content.....	none
Blush Resistance.....	Excellent
Solvent Resistance.....	Good
Concrete Adhesion.....	Superior (over sealed surfaces)



Surface Koatings, Inc.
134 Davis Street
Portland, TN 37148
Ph: 615.323.9461 Fax: 615.323.9816