

CITRUS STRIP

PRODUCT CODE: 009-CTSTP

CITRUS BASED SOLVENT ACRYLIC COATING STRIPPER

PRODUCT DESCRIPTION

Citrus Strip is a concentrated, water soluble, citrus based stripper, detergent/degreaser formulated using natural citrus products in conjunction with powerful organic, biodegradable solvents specially blended to outperform most conventional petroleum based solvents, plus have the advantage of the ability to be diluted with water. Citrus Strip is designed to emulsify acrylic coatings to allow stripping capabilities. This product will remove most resins, adhesives, printing inks, decals, dirt, soil, and most petroleum based substances such as tar, asphalt, grease, oil, and rubber tire marks.

BENEFITS/FEATURES

- ◆ Can be used as a highly concentrated degreaser/cleaner.
- ◆ Formulated as an economical means of stripping acrylic coatings as apposed to costly soy based products.
 - ◆ This product's stripping capabilities can save money over high cost mechanical stripping methods.

RECOMMENDED APPLICATIONS

Citrus Strip is recommended for stripping acrylic coatings applied to interior or exterior concrete surfaces.

TECHNICAL INFORMATION

Solids.....	0%	Wet Appearance.....	Clear
Drying Time.....	Refer to Directions	Dry Appearance.....	n/a
Re-Coat Time.....	Refer to Directions	VOC Content.....	none
Foot Traffic.....	Refer to Directions	Blush Resistance.....	n/a
Wheel Traffic.....	Refer to Directions	Solvent Resistance.....	n/a
Application Temp.....	40°F - 85°F	Concrete Adhesion.....	n/a

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES

Citrus Strip is VOC and OTC compliant in all areas of the United States and many foreign nations.

APPROXIMATE COVERAGE RATES

<u>Application Surface</u>	<u>First Coat</u>	<u>Optional Second Coat</u>
Acrylic Coated Surfaces	100-150 ft ²	100-150 ft ²

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

SHELF LIFE

Citrus Strip has a shelf life of up to two years in it's original, sealed, unopened container.

PACKAGING

Citrus Strip is packaged and stocked in 1 gallon cans, 5 gallon pails, and 55 gallon drums.

SURFKOAT™

SURFACE KOATINGS, INC.

12049 A Lebanon Rd. Mount Juliet, TN 37122
Phone: (615) 773-1616 Fax: (615) 773-1457
Visit us online at: www.SurfKcoat.com

CLEANING PRODUCTS

CITRUS STRIP

INSTRUCTIONS FOR USE

Preparation: Sweep the area to be cleaned free of trash and debris. Protect all areas not to be cleaned or stripped. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If needed, use a plastic or coated cardboard as a spray shield. Be sure all pilot lights, arcing or sparking devices are off. No Smoking!

1. Apply Citrus Strip by spray method liberally over acrylic coated concrete surface to be stripped at an approximate coverage rate of 100-150 square feet per gallon.
2. Allow stripper to penetrate and emulsify coating for approximately 20-45 minutes depending on area temperature and relative humidity.
3. For coatings on slick finished floors, a scraper may be used to remove excess coating. Add a small amount of water and scrub vigorously to remove emulsified (liquefied) coating. Heavily coated areas may also require a second treatment.
4. Flush the stripped area with water. Rinse and mop up or use a wet shop vac to remove existing coating. When removing exterior coatings, a high PSI and GPM commercial use pressure washer may be used to remove emulsified coating.
5. Once dry, the floor is ready to apply coatings.

Please note: Acrylic coatings can be trapped in the pores of a concrete surface. Mechanical means of profiling the floor may be necessary to apply some stains or coatings. Test prior to stain or coating application.

CLEAN-UP

Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL

Not applicable.

PRECAUTIONS AND LIMITATIONS

- ▶ Citrus Strip will not freeze, however, it is recommended to store in an area between 50 F and 85 F recommended.
- ▶ Citrus Strip will only strip acrylic coatings. Not recommended to strip epoxies or urethanes.
- ▶ Citrus Strip is combustible and flammable. Do not smoke.
- ▶ Citrus Strip contains solvents such as Glycol Ethers. Abide by recommended safety guidelines.
- ▶ Coverage rates depend upon many conditions including application method, surface porosity, applicator, ect.
- ▶ Citrus Strip was designed for interior concrete and exterior concrete concrete surfaces.
- ▶ Citrus Strip may be diluted. Note, the higher the dilution rate, the less strength to clean or strip.

SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 615-773-1616.

SURFKOAT™

SURFACE KOATINGS, INC.

12049 A Lebanon Rd. Mount Juliet, TN 37122
Phone: (615) 773-1616 Fax: (615) 773-1457
Visit us online at: www.SurfKcoat.com