

SFRS SYSTEM SPECIFICATIONS

MODEL	DAILY PROD. GALLONS (Approx.)	DAILY PROD. CARS (Approx.)	3rd YEAR OPERATING PRESSURE	INLET SIZE	R.O. ELEMENTS	DESIGNED RECOVERY	MEMBRANE PUMP HORSEPOWER	REPRESSURIZATION PUMP HORSEPOWER
SFRS-800	800	50-125	200	1/2"	1 (4" X 21")	35%	.5hp @ 115v	.5hp @ 115v
SFRS-1500	1500	125-200	185	3/4"	1 (4" x 40")	40%	1.5hp @ 230v	1.5hp @ 230v
SFRS-3000	3000	200-450	189	3/4"	2 (4" x 40")	40%	1.5hp @ 230v	.5hp @ 115v
SFRS-4500	4500	400-600	194	3/4"	3 (4" x 40")	40%	3.0hp @ 230v	.5hp @ 115v
SFRS-6000	6000	600-1000	198	3/4"	4 (4" x 40")	40%	3.0hp @ 230v	1.0hp @ 115v

SYSTEM REQUIREMENTS

MODEL	SPOT FREE R.O. FOOT PRINT	STORAGE TANK SIZE (Typical)	TOTAL FOOTPRINT REQUIRED	TOTAL ELECTRICAL (KW) REQUIRED	SPOT FREE RO & PUMP SHIPPING WEIGHT
SFRS-800	1' X 3'	500	17 square Feet	3.5	108 lbs.
SFRS-1500	2' x 4'	1000	36 square Feet	3.5	190 lbs.
SFRS-3000	2' x 4'	2000	55 square feet	3.5	225 lbs.
SFRS-4500	2' x 4'	3000	55 square feet	6.0	250 lbs.
SFRS-6000	2' x 4'	4000	66 square feet	7.0	270 lbs.

TYPICAL INSTALLATION

