



MONIMAX 5100 T ATM

Get more value with the economical, high performance, and multipurpose ATM

Features

- **Multipurpose**

Monimax 5100 T fits into all ATM applications: walk-up or drive-up, kiosk and through-the wall, on-premise and off-premise. It gives you true flexibility.

- **High performance**

Built on the Windows open platform, it can deliver multimedia advertisements and decrease transaction time. Thanks to its scalable hardware and software, advanced services and functions can be easily added.

- **Under any sunlight**

Its 10.4" sunlight viewable color display supports perfect operation under any exterior environment. Not to mention *Monimax 5100T* is fully weatherized.

- **Easy to operate**

Compact architecture and small footprint make installation simple and maintenance easy.

Monimax 5100T can be upgraded with additional features and security

Monimax 5100T provides various optional modules such as sunlight viewable LCD display, supports up to 4 cassettes, electronic or Cencon lock and 5.7" supervisor display.

Monimax 5100T ensures the complete security for the cardholder and financial institution with Triple DES, VISA/PCI certified EPP, UL291 business hours and optional UL291 level 1 safe, and voice guidance system to meet ADA requirements.



Adding Value to Your Business

Create your true ATM values Design your own ATM portfolio

System Control

Intel® Pentium—IV Processor, Microsoft®
Windows® XP Platform

Communication

TCP/IP (SSL configurable), Optional:
Dial-up, wireless connection

Application Software

NDC+, DDC912

Customer Display

10.4" Colour TFT LCD
Optional: sunlight viewable

Input Type

4x2 Function keys
4x4 Numeric keys
VISA/PCI EPP (Encrypting PIN pad) DES, T-DES,
ADA compliant

Supervisor Operation

2 lines of 10 characters/line LCD, Portable type, 16 keys, Op-
tional: 5.7" mono display
4x2 function keys, 16 keys

Card Handling

Dip type card reader, Optional: EMV Level 1, 2 compliant

Cash Dispensing

2000 notes cassette (up to 4 Cassettes)
200 notes reject bin

Printers

Graphical thermal receipt printer

Security

UL 291 Business hours
Electronic lock
Voice Guidance System
Optional: UL 291 Level 1
KABA Mas Cencon safe lock

Power Supply

AC 110-230V, 50-60 Hz



Operating environment

Temperature
0°C-40°C
Optional: -10°C-40°C
Humidity
25%-86%

Dimensions and Weight

Height: 1500mm
Width: 600mm
Depth 828mm
Weight: 200kg
(when it has UL291 Business Hour safe)



740/2 Broome St, Waterloo NSW 2017, ABN: 72 111 571 076, Free phone: 1800 MR ATMS, Mobile:
0425 376 184 (ask for Mark), Email: sales@mandrakeatm.com, Web: www.mandrakeatm.com